

BS130N Battery 12 V 12 Ah



# **Details**

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechangeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS130N Battery 12 V 12 Ah

# **Technical specifications**

#### **Electrical Characteristics**

Nominal voltage	12 V
Nominal capacity	11 to 20 Ah
Internal approx.	13 mOhm
resistance	

# Charge / discharge

<u> </u>	
Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	3.6 A
Max. discharge current	60 A

#### Temperature

Charging temperature	0 to +40°C	
Discharging temperature -15 to +50°C		

# General

Product type	Sealed lead acid battery	

# Physical

Physical dimensions	151 x 98 x 98 mm
Net weight	4.27 kg
Shipping weight	4.27 kg
Material	ABS
Terminal type	Fast-on 6.35 mm

# Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

# Standards & regulation

Compliancy	CE, RoHS 2, WEEE
Certification	VdS

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

