

# C-9403

## Conventional Sounder, Multi Tone, Shallow Base w/ Visual Indicator

### General

---

The C-9403 is conventional sounder with VID is an audible fire alarm device with a high intensity LED visual indicator bank. It gives an audible and visual alarm signal when 24 VDC is applied to its inputs.



### Details

---

- High sound output
- 2 User selectable tones
- Shallow mounting base with optional deep base
- Two part construction with base mounted termination for easy installation
- LPCB marked

# C-9403

## Conventional Sounder, Multi Tone, Shallow Base w/ Visual Indicator

### Technical specifications

#### General

Compatibility	GST conventional systems
---------------	--------------------------

#### Electrical

Power supply type	24 VDC
Operating voltage	20 to 28 VDC (24 VDC typical)
Current consumption	≤ 35 mA

#### Sounder

Output level	≥ 95 dB @ 1 m Continuous
Frequency	Selectable
Selectable tones	2

#### VID

Colour	Red
Flash frequency	2 Hz (±20%)

#### Physical

Physical dimensions	110 x 95.9 mm (Ø x H)
Shipping weight	327.2 g
Colour	Red
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Shallow
Cable size	> 1.5 mm <sup>2</sup>
Material	ABS

#### Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	< 95% non-condensing
Environment	Indoor
IP rating	IP33C

#### Standards & regulation

Compliance	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-3

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 18 May 2020 - 12:44

