

DM970

Apollo XP95 Series Intrinsically Safe MCP - Red Without Flap (55000-940)

General

The DM970 is an intrinsically safe manual call point. It should be used together with the PT971/2 protocol translator and GBX70 barrier. It is based on a standard weatherproof manual call point and features an "interrupt" facility to provide fast response to an alarm.

Application

When activated, the intrinsically safe call point interrupts the polling cycle to indicate to the control panel that it has been operated. Becuase of this feutre, an alarm can be reported in less than 0.2 seconds. The DM970 has the same operating characteristics as the standard manual call point versions. It is a red, break-glass call point to which a protective lift-up flap may be added as an option.



Details

- Easy to install
- May be used with break glass or resettable element
- Easy to replace glass
- High quality micro switch
- Back box included
- IP67 rated
- BASEEFA certified



Apollo XP95 Series Intrinsically Safe MCP - Red Without Flap (55000-940)

Technical Specifications

Electrical	
Operating voltage	14 to 22 VDC
Physical	
Physical dimensions	124 x 124 x 60 mm
Net weight	± 400 g
Colour	Red
Colour	Red
Dimensions	124mm x 124mm x 60mm
Weight	± 400 g
Environmental	
Operating temperature	-20 to +40°C (T5) / -20 to +60°C (T4)
Storage temperature	-30 to +80°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor, IS
IP-rating	IP67
Operating temperature	-20°C to +40°C (T5) -20°C to +60°C (T4)
Storage temperature	-30°C to +80°C
Relative humidity (no	0 to 95 %
condensation)	
IP rating	IP67
Standards & Regulation	
Certification	EN54-11
Operating voltage	
Supply voltage	14 - 22 VDC
Current consumption	
Quiescent current	230μΑ
Alarm	4 mA
Alarm indication (LED)	
Red	
Approval	
BASEEFA	BAS02ATEX1290
Classification	E Ex ia IIc T5

