

EST-PSM48

Power Supply Manager

Overview

EST-PSM48 Power Supply Manager is designed for distribution of DC Power Supply from Power Supply Units (PSU) and a back-up battery. The unit controls battery charging and distributes power supply to all Voice Evacuation System (VES) equipment at max 60 A. When the system uses battery back-up, the power supplied is 3.2 kW (48 V).

The unit complies with the EN 54-4 VES standards and also EN 12101-10 Smoke and Heat Control System standards.

As a main source of energy distribution, the manager uses external modules 800 W (EST-PS48800) for 48 V.

As a source of stand-by power supply it uses the battery bank of the capacity of up to 200 Ah.

EST-PSM48 cooperates with the 4 x 12 V VRLA battery bank. It maintains the bank in charged condition, ensures temperature compensation of charging parameters and monitors serial resistance of the battery and its wiring as specified in Exhibit No. A2 to the EN 54-4 Standard.

EST-PSM48 co-operates with up to 4 modules of EST-PS4880 Power Supply Units. The manager ensures safe connection for the purpose of parallel operations and monitors the output parameters of each power supply unit.

EST-PS48800 is designed for assembling in a dedicated EST-PF4 Power Supply Unit Frame. The elements of the system are designed for assembling in a Rack 19" IP30-type.



EST-PSM48

Power Supply Manager

Technical specifications

Electrical

Power consumption	885 W max. (3.85 A)
AC power supply	230 VAC +10% -15%, 50/60 Hz
Efficiency at rated power	> 90%
DC input	4; bolted terminals; dedicated power supply unit EST-PS48800
DC input protection	4 x 20 A 58 VDC
DC outputs	8 x 48 V, each output max 30 A (total for all 8 outs max. 63 A)
Summary maximum DC output load (24 V and 52 V)	3200 W
Charging current	max. 14 A
Charging voltage	54.6 V \pm 0.6 V (at 25°C)
Maximum resistance of wiring and fuses	10 m Ω
Maximum total serial resistance of wiring, fuses, and batteries	28 - 100 m Ω

Physical

Physical dimensions	482 x 85 x 443 mm (W x H x D)
Net weight	7.2 kg
Type of mount	19" rack
Maximum configuration	1x EST-PSM48 - Power Supply Manager 4x EST-PS4880 - Power Supply Unit 1x EST-PF4 - Power Supply Units Frame
Battery (type)	4 pieces, VRLA 12 V 15-200 Ah

Environmental

Operating temperature	-5°C to +40°C
IP rating	30

Standards & regulation

Certification	EN54-4
Standards	EN12101-10

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 7 October 2019 - 16:14



**United
Technologies**

Climate | Controls | Security