



IO2031C

2000 Series Input Output Unit - 2 Input 1 Output (CPD Approved)

General

The IO2031C is a 2000 series addressable 2 input/1 output unit with selectable line supervision and 1 magnetically latched output. The unit is loop powered and supplied in an enclosure for surface mounting applications.

The 2000 series loop powered Input/Output modules are designed to provide unlimited applications to input monitoring and output switching. These modules combined with the powerful features of the 2000/1200 series fire panels gives the user total versatility for all applications.

Configuration

The IO2031C IO unit operates on a 2000/1200 series loop to monitor input contacts and independently switch relay outputs for control of equipment. Each I/O module occupies only one address on the addressable loop regardless of the number of inputs or outputs on that module.

All 2000 series devices utilize an advanced digital data communications protocol with extensive error correction algorithms to ensure system reliability. Up to 128 devices may be installed on every communication loop. Device addressing is via two convenient, easy to use, rotary switches.

Inputs

Any input may be wired as supervised or as unsupervised, normally open or normally closed contacts. The IO unit will report four states back to the panel for every input: Open, Passive, Active or Short circuit. Depending on the programming of the fire panel, actions can be taken for any one of these states.

Outputs

The output is a magnetically latched relay providing a potential free changeover contact. Because it is magnetically latched, the output does not consume any additional power in either the active or passive state.



Standard Features

- Wide range of I/O Modules : 2 input-1 output / 2 input-2 output / 4 input / 4 input - 4 output
- Versatile input structure
- Supervised inputs
- Normally Open/Normally Closed operation
- Magnetic latched output relay
- Loop powered
- Easy numeric addressing
- EN54 and CPD certified

IO2031C

2000 Series Input Output Unit - 2 Input 1 Output (CPD Approved)

Specifications

Power supply

Operating voltage	17 - 39 VDC
Current (standby)	< 300 μ A
Current (max)	350 μ A

Electronics

Outputs (un supervised)	1 (2 A @ 30 VDC)
Inputs (supervision selectable)	2
Operating modes	Normal, Active, Open, Short
EOL resistor (if required)	150 k Ω , 1/4 W, 5%
Input resistor	33 k Ω , 1/4 W, 5%

Housing

Size (l x w x h)	175 x 124 x 51 mm
Material	White plastic

Environmental

Storage temperature	-20°C to +60°C
Operating temperature	-5°C to +40°C
Relative humidity (non-condensing)	10 to 95%
IP rating	IP40

Installation

Wiring	2-core
Quantity (max)	128 per loop

Ordering Information

Part No.	Description
IO2031C	2000 Series Input Output Unit - 2 Input 1 Output (CPD Approved)

