

TVM-2212

TRUVISION 22" LED, VGA, HDMI, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market. Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

Capabilities

The TVM-2212 is a 22" class monitor, offering HDMI and VGA connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



Details

- 22" LED BacklightFull HD resolution

- 16:9 aspect ratio
 1920 x 1080 recommended resolution
- 1,000:1 contrast ratio for crisp images
 3D comb filter for optimal image quality
 Multiple inputs including VGA, HDMI

TVM-2212
TRUVISION 22" LED, VGA, HDMI, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Technical Specifications

Display	
Screen Size	21.5"
Aspect Ratio	16:9
Contrast Ratio	1,000:1
Viewing Angle (H/V)	170° / 160°
Response Time	5ms
Brightness	250 cd/m ² (typ)
Video Compatibility	NTSC/PAL Auto Detect
Recommended Resolution	1920 x 1080 @ 60 HZ
Audio	
Speaker Power	2W x 2
Speakers	Built-in
Interfoce	
Interface	
BNC Video I/O	No
VGA Video In (15-pin d- sub)	Yes
HDMI Video In	1
RCA Audio In	1
PC Stereo In	Yes
Head Phone Out	No
Operations	
Controls	Power, Up/Down, Left/Right, Source, OSD Menu
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish,
Barrata Cartari Communi	Polish
Remote Control Support	Yes
General	
Technology	LED
VESA compatibility	100 x 100 mm
Filter Type	3D Combfilter, Deinterlace
Accessories Included	Manual, Power Cord, Remote Control
Panel Lamp Life	30,000 hours
Electrical	
Power supply type	100 to 240 VAC
Power consumption	<30W
Physical	
	E12mm v 272mm v 150mm
Physical dimensions	512mm x 372mm x 150mm
Net weight	3.9 kg
Shipping weight Colour	5.3 kg
	Black Plastic
Housing Type	Flastic
Environmental	
Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Relative humidity	10 to 85%
Environment	Indoor
Standards & Regulations	
Compliancy	CE
F/	

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.



