

TVM-3202

TRUVISION 32" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market. Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

Capabilities

The TVM-3202 is a 32" class monitor, offering HDMI, VGA and BNC connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



Details

- 32" LED BacklightFull HD resolution
- 16:9 aspect ratio
 1920 x 1080 recommended resolution
- 1,000:1 contrast ratio for crisp images
 3D comb filter for optimal image quality
 Multiple inputs including BNC, VGA, HDMI
 BNC analog input

TVM-3202 TRUVISION 32" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

Technical Specifications

Display	
Screen Size	31.5"
Aspect Ratio	16:9
Contrast Ratio	1,000:1
Viewing Angle (H/V)	178° / 178°
Response Time	8ms
Brightness	300 cd/m ² (typ)
Video Compatibility	NTSC/PAL Auto Detect
Recommended Resolution	n 1920 x 1080 @ 60 HZ
Audio	
Speaker Power	2W x 2
Speakers	Built-in
Internet and a	
Interface	
BNC Video I/O	1/1
VGA Video In (15-pin d-	Yes
sub)	
HDMI Video In	1
RCA Audio In	1
PC Stereo In	Yes
Head Phone Out	No
Operations	
Controls	Power, Up/Down, Left/Right, Source, OSD Menu
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish
Remote Control Support	Yes
General	
Technology	LED
VESA compatibility	100 x 100 mm
Filter Type	3D Combfilter, Deinterlace
Accessories Included	Manual, Power Cord, Remote Control
Panel Lamp Life	30,000 hours
Electrical	
Power supply type	100 to 240 VAC
Power consumption	<45W
Physical	
Physical dimensions	729mm x 551 mm x 245mm
Net weight	8.2 kg
Shipping weight	10.5 kg
Colour	Black
Housing Type	Plastic
Environmental	
Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Relative humidity	10 to 85%
Environment	Indoor
Standards & Regulat	ions
Compliancy	CE



As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

United Technologies Climate | Controls | Security