

## TVM-4002

TRUVISION 40" LED, VGA, HDMI, BNC, Audio Speaker,  
Stereo Audio In, FULL HD, 1920X1080

### Overview

The LED TVM range of monitors is the latest advancement in TruVision monitors. Providing superior image quality through HDMI, VGA and BNC connections, these monitors are a great fit for today's demanding video surveillance market. Whether displaying analog or IP resolutions, these monitors are designed to provide top image quality paired with industrial reliability.

These monitors are designed to perform 24/7 and are design with security applications in mind.

### Capabilities

The TVM-4002 is a 40" class monitor, offering HDMI, VGA and BNC connections. The monitor has two built in speakers and is provided with VESA wall mount holes, making them easy to combine with a variety of TruVision mounting accessories. The on screen display allows for full control of images settings such as brightness, contrast and colour temperature.



### Details

- 40" LED Backlight
- Full HD resolution
- 16:9 aspect ratio
- 1920 x 1080 recommended resolution
- 5,000:1 contrast ratio for crisp images
- 3D comb filter for optimal image quality
- Multiple inputs including BNC, VGA, HDMI
- BNC analog input

# TVM-4002

TRUVISION 40" LED, VGA, HDMI, BNC, Audio Speaker, Stereo Audio In, FULL HD, 1920X1080

## Technical Specifications

### Display

Screen Size	39.5"
Aspect Ratio	16:9
Contrast Ratio	5,000:1
Viewing Angle (H/V)	178° / 178°
Response Time	8ms
Brightness	360 cd/m <sup>2</sup> (typ)
Video Compatibility	NTSC/PAL Auto Detect
Recommended Resolution	1920 x 1080 @ 60 HZ

### Audio

Speaker Power	2W x 2
Speakers	Built-in

### Interface

BNC Video I/O	1/1
VGA Video In (15-pin d-sub)	Yes
HDMI Video In	1
RCA Audio In	1
PC Stereo In	Yes
Head Phone Out	No

### Operations

Controls	Power, Up/Down, Left/Right, Source, OSD Menu
OSD	English, French, Spanish, German, Italian, Portuguese, Netherlands, Russian, Turkish, Polish
Remote Control Support	Yes

### General

Technology	LED
VESA compatibility	100 x 100 mm
Filter Type	3D Combfilter, Deinterlace
Accessories Included	Manual, Power Cord, Remote Control
Panel Lamp Life	30,000 hours

### Electrical

Power supply type	100 to 240 VAC
Power consumption	<60W

### Physical

Physical dimensions	907mm x 610 mm x 245mm
Net weight	11 kg
Shipping weight	13.8 kg
Colour	Black
Housing Type	Plastic

### Environmental

Operating temperature	0 to 40°C
Storage temperature	-20 to 60°C
Relative humidity	10 to 85%
Environment	Indoor

### Standards & Regulations

Compliance	CE
------------	----

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

