



Date: August 9, 2019

**CERTIFICATE OF COMPLIANCE**

| This certificate of compliance validates the following |                                                           |                     |                                                                                       |
|--------------------------------------------------------|-----------------------------------------------------------|---------------------|---------------------------------------------------------------------------------------|
| TEST REPORT NUMBER                                     | 1. 1439/BA/19<br>2. 1927/BA/16                            | CERTIFICATE NUMBER  | DC - UAE - 0130                                                                       |
| DATE OF ISSUE                                          | 1. April 8, 2019<br>2. March 28, 2017                     | DATE OF ISSUE       | August 9, 2019                                                                        |
| DATE OF EXPIRY                                         | Not applicable                                            | DATE OF EXPIRY      | June 26, 2029                                                                         |
| Manufacturer details                                   |                                                           |                     |                                                                                       |
| NAME OF FACTORY / MANUFACTURER                         | Ambient - System Sp. z o.o.                               | NAME OF THE BRAND   | Edwards                                                                               |
| FACTORY ADDRESS / REGION                               | ul. Galaktyczna 37<br>80-299 Gdańsk<br>Republic of Poland | MODEL / NO          | EST VES                                                                               |
| WEBSITE                                                | www.firesecurityproducts.com                              | LOGO ON THE PRODUCT |  |
| TELEPHONE                                              | +34 93 480 27 78                                          | EMAIL               | secretariaat.nederland@fs.utc.com                                                     |






| Product Details From Test Report |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Reference Test Report Page No.          |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|
| DESCRIPTION OF THE PRODUCT       | Voice alarm control and indicating equipment with integrated power supply equipment<br>(Detailed specification below)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 3                                       |
| TESTS STANDARD                   | EN 54-16:2008 Fire detection and fire alarm systems - Part 16: Voice alarm control and indicating equipment<br>EN 54-4:1997 + AC:1999 + A1:2002 + A2:2006 Fire detection and fire alarm systems -<br>Part 4: Power supply equipment                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 8<br>(1439/BA/19)<br>10<br>(1927/BA/16) |
| TESTS DESCRIPTION                | Requirements, test methods and performance criteria for voice alarm control and indicating equipment with integrated power supply equipment intended to broadcast a warning of fire between a fire detection and fire alarm system and the occupants of a building.                                                                                                                                                                                                                                                                                                                                                                                                                   | 8<br>(1439/BA/19)<br>10<br>(1927/BA/16) |
| SPECIFICATION OF TEST SPECIMEN   | Voice alarm control and indicating equipment type EST VES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3-7<br>(1439/BA/19)                     |
|                                  | VACIE components:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | ➢ Amplifier                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                         |
|                                  | ➢ Emergency microphone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                         |
|                                  | ➢ Others                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                         |
|                                  | 2x160W RMS, 2x320W RMS<br>EST-DFMS with extension type EST-EKB-20M, EST-DFMS BOX,<br>EST-DFMS BOX-L<br>EST-VES-2001, EST-VES-2001L, EST-VES-2001N, EST-VES-2001LN,<br>EST-VES-4001, EST-VES-4001L, EST-VES-4001N, EST-VES-4001LN,<br>EST-VES-4002, EST-VES-4002L, EST-VES-4002N, EST-VES-4002LN,<br>EST-xNET_MINI-1Gb/WAN/RS, EST-xNET_MINI-1Gb/WAN,<br>EST-xCtrlLine-2, GST-xCtrlLine-4, SF-MM31002D-GP,<br>SF-MM31/55WD055D-GP, SF-MM31/55WD055-GP,<br>SF-MMS31/55WD055D-GP, SF-MMS31/55WD055-GP,<br>SF-SM31/55WD020D-GP, SF-SM31/55WD020D-GP,<br>SF-SMS31/55WD020D-GP, SF-SM531/55WD020-GP,<br>EST-xLCD, EST-REG1, ST-POE8P-A, ST-POE4P-A,<br>ST-POE1R-P, FS116P, FS116Pv2, FS108P |                                         |
|                                  | Cabinet:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                         |
|                                  | EST VES, EST-DFMS BOX, EST-DFMS BOX-L: 350 x 440 x 525 mm<br>EST-CEXT: 350 x 440 x 280 mm<br>EST-DFMS: 210 x 150 x 55 mm<br>EST-EKB-20M: 210 x 120 x 55 mm<br>EST-DMS: 210 x 120 x 55 mm<br>EST-DMS-LCD: 210 x 150 x 55 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                         |
|                                  | Installation:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                         |
|                                  | One cabinet (or several interconnected) or several cabinets arranged in a protected area, wall-mounted.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                         |
|                                  | Output power:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                         |
|                                  | 2x160W RMS: 2x160W, 2x320W RMS: 2x320W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                         |
|                                  | Software version:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | 1.1.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | Power supply equipment integrated with voice alarm control and indicating equipment type EST VES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                         |
|                                  | Product type:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                         |
|                                  | integrated                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                         |
|                                  | Type of power supply:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | electric                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                         |
|                                  | Operating temperature:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                         |
|                                  | -5°C + +40°C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                         |
|                                  | IP protection:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                         |
|                                  | IP30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                         |
|                                  | Enclosure type and dimensions<br>(Length x Width x Height)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                         |
|                                  | power supply equipment is located in the housing at the voice alarm control and indicating equipment type EST VES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | Output operating current $I_{max}$ a:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | 0,15 A (for the output 24 V DC)<br>0,35 A (for the output 48 V DC)<br>0,35 A (for the output PoE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | Output operating current $I_{max}$ c:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | 0,15 A (for the output 24 V DC)<br>0,35 A (for the output 48 V DC)<br>0,35 A (for the output PoE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | Output circuits: range of output voltage:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                         |
|                                  | 22 + 27 V DC (for the output 24 V DC)<br>42 + 54 V DC (for the output 48 V DC)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                         |
|                                  | Main supply                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                         |
|                                  | Main supply: supply voltage:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                         |
|                                  | 230 V AC (-15% + +10%)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                         |
|                                  | Input circuits: number of inputs:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                         |
|                                  | Maximum current consumption:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                         |
|                                  | 2,9 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | Reserve supply                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                         |
|                                  | Power Supply: Battery type:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                         |
|                                  | lead-acid                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                         |
|                                  | Maximum current of battery charging:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                         |
|                                  | 2,2 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | Maximal internal resistance of the battery and elements connected to the battery circuit:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                         |
|                                  | 65 mΩ for battery capacity > 40 Ah<br>80 mΩ for battery capacity > 24 Ah<br>100 mΩ for battery capacity > 17 Ah                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                         |
|                                  | Maximum battery capacity:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                         |
|                                  | 42 Ah                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                         |
|                                  | Battery charge voltage in floating mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                         |
|                                  | 2,6 V DC in temperature 25°C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                         |
|                                  | Temperature compensation in floating mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                         |
|                                  | yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                         |
|                                  | Restrictions on the use the certificate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                         |
|                                  | Power supply equipment can be only used for installation in VACIE type EST VES.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                         |



|                               |                          |                                                                                                                                                                                                                               |      |                                            |
|-------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|--------------------------------------------|
| TESTS RESULTS                 | EN 54-16                 | General requirements                                                                                                                                                                                                          | PASS | 8<br>(1439/BA/19)<br>12-26<br>(1927/BA/16) |
|                               | EN 54-16                 | General requirements for indications                                                                                                                                                                                          | PASS |                                            |
|                               | EN 54-16                 | Voice alarm condition                                                                                                                                                                                                         | PASS |                                            |
|                               | EN 54-16                 | Voice alarm manual control                                                                                                                                                                                                    | PASS |                                            |
|                               | EN 54-16                 | Emergency microphone(s)                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-16                 | Signal-to-noise ratio                                                                                                                                                                                                         | PASS |                                            |
|                               | EN 54-16                 | Frequency response of VACIE without microphone(s)                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-16                 | Frequency response of VACIE with microphone(s)                                                                                                                                                                                | PASS |                                            |
|                               | EN 54-16                 | Reception and processing of fire signals                                                                                                                                                                                      | PASS |                                            |
|                               | EN 54-16                 | Delays to entering the voice alarm condition                                                                                                                                                                                  | PASS |                                            |
|                               | EN 54-16                 | Output to fire alarm devices                                                                                                                                                                                                  | NA   |                                            |
|                               | EN 54-16                 | Emergency microphone(s)                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-16                 | General requirements                                                                                                                                                                                                          | PASS |                                            |
|                               | EN 54-16                 | General requirements for indications                                                                                                                                                                                          | PASS |                                            |
|                               | EN 54-16                 | The quiescent condition                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-16                 | The voice alarm condition                                                                                                                                                                                                     | PASS |                                            |
|                               | EN 54-16                 | Fault warning condition                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-16                 | Disablement condition                                                                                                                                                                                                         | PASS |                                            |
|                               | EN 54-16                 | Interface to external control device(s)                                                                                                                                                                                       | NA   |                                            |
|                               | EN 54-16                 | Emergency microphone(s)                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-16                 | Design requirements                                                                                                                                                                                                           | PASS |                                            |
|                               | EN 54-16                 | Additional design requirements for software controlled VACIE                                                                                                                                                                  | PASS |                                            |
|                               | EN 54-16                 | Output power                                                                                                                                                                                                                  | PASS |                                            |
|                               | EN 54-16 - EN 60068-2-1  | Cold (operational)                                                                                                                                                                                                            | PASS |                                            |
|                               | EN 54-16 - EN 60068-2-75 | Impact (operational)                                                                                                                                                                                                          | PASS |                                            |
|                               | EN 54-16 - EN 60068-2-6  | Vibration, sinusoidal (operational)                                                                                                                                                                                           | PASS |                                            |
|                               | EN 54-16 - EN 60068-2-6  | Vibration, sinusoidal (endurance)                                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-16 - EN 54-4       | Supply voltage variation                                                                                                                                                                                                      | PASS |                                            |
|                               | EN 54-16 - EN 50130-4    | Electromagnetic compatibility (EMC), immunity tests (operational)                                                                                                                                                             | PASS |                                            |
|                               | EN 54-16 - EN 60068-2-78 | Damp heat, steady state (operational)                                                                                                                                                                                         | PASS |                                            |
|                               | EN 54-16 - EN 60068-2-78 | Damp heat, steady state (endurance)                                                                                                                                                                                           | PASS |                                            |
|                               | EN 54-16                 | Audible warning                                                                                                                                                                                                               | NA   |                                            |
|                               | EN 54-16                 | Delays to entering the voice alarm condition                                                                                                                                                                                  | PASS |                                            |
|                               | EN 54-16                 | Phased evacuation                                                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-16                 | Manual silencing of the voice alarm condition                                                                                                                                                                                 | PASS |                                            |
|                               | EN 54-16                 | Manual reset of the voice alarm condition                                                                                                                                                                                     | PASS |                                            |
|                               | EN 54-16                 | Output to fire alarm devices                                                                                                                                                                                                  | NA   |                                            |
|                               | EN 54-16                 | Voice alarm condition output                                                                                                                                                                                                  | PASS |                                            |
|                               | EN 54-16                 | Indication of faults related to transmission path to the VACIE                                                                                                                                                                | PASS |                                            |
|                               | EN 54-16                 | Indication of faults related to voice alarm zones                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-16                 | Disablement condition                                                                                                                                                                                                         | PASS |                                            |
|                               | EN 54-16                 | Voice alarm manual control                                                                                                                                                                                                    | PASS |                                            |
|                               | EN 54-16                 | Interface to external control device(s)                                                                                                                                                                                       | NA   |                                            |
|                               | EN 54-16                 | Emergency microphone(s)                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-16                 | Redundant power amplifiers                                                                                                                                                                                                    | PASS |                                            |
| PRODUCT APPLICATION GUIDELINE | EN 54-4                  | General requirements                                                                                                                                                                                                          | PASS | 8<br>(1439/BA/19)<br>23-26<br>(1927/BA/16) |
|                               | EN 54-4                  | Functions                                                                                                                                                                                                                     | PASS |                                            |
|                               | EN 54-4                  | Materials, design and manufacture                                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-4                  | General requirements                                                                                                                                                                                                          | PASS |                                            |
|                               | EN 54-4                  | Functions                                                                                                                                                                                                                     | PASS |                                            |
|                               | EN 54-4                  | Materials, design and manufacture                                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-4                  | Documentation                                                                                                                                                                                                                 | PASS |                                            |
|                               | EN 54-4                  | Marking                                                                                                                                                                                                                       | PASS |                                            |
|                               | EN 54-4 - EN 60068-2-1   | Cold (operational)                                                                                                                                                                                                            | PASS |                                            |
|                               | EN 54-4 - EN 60068-2-75  | Impact (operational)                                                                                                                                                                                                          | PASS |                                            |
|                               | EN 54-4 - EN 60068-2-6   | Vibration, sinusoidal (operational)                                                                                                                                                                                           | PASS |                                            |
|                               | EN 54-4 - EN 60068-2-6   | Vibration, sinusoidal (endurance)                                                                                                                                                                                             | PASS |                                            |
|                               | EN 54-4 - EN 50130-4     | Electromagnetic compatibility (EMC), immunity tests (operational)                                                                                                                                                             | PASS |                                            |
|                               | EN 54-4 - EN 60068-2-78  | Damp heat, steady state (operational)                                                                                                                                                                                         | PASS |                                            |
|                               | EN 54-4 - EN 60068-2-78  | Damp heat, steady state (endurance)                                                                                                                                                                                           | PASS |                                            |
|                               | rev.05.2019              | The EST VES is a certified alarm system for buildings. Wall-mounted EST VESs can broadcast messages, audit and alarms in one, several or all areas of a building, as an evacuation signal in case of fire or other emergency. |      |                                            |
|                               |                          |                                                                                                                                                                                                                               |      |                                            |



| Laboratory and Certification Body Details              |                                                                                                                      |                                     |                                                                                                                                                                                                                                      |
|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME OF CERTIFICATION BODY                             | CNBOP-PIB<br>Centrum Naukowo-Badawcze<br>Ochrony Przeciwpożarowej<br>Państwowy Instytut Badawczy                     | NAME OF TEST FACILITY               | CNBOP-PIB<br>Zespół Laboratoriów Sygnalizacji<br>Alarmu Pożaru<br>i Automatyki Pożarniczej                                                                                                                                           |
| CERTIFICATION BODY<br>ADDRESS / REGION                 | ul. Nadwiślańska 213<br>05-420 Józefów<br>REPUBLIC OF POLAND                                                         | TEST FACILITY<br>ADDRESS / REGION   | ul. Nadwiślańska 213<br>05-420 Józefów<br>REPUBLIC OF POLAND                                                                                                                                                                         |
| WEBSITE                                                | www.cnbop.pl                                                                                                         | WEBSITE                             | www.cnbop.pl                                                                                                                                                                                                                         |
| TELEPHONE                                              | +48 22 769 33 47                                                                                                     | TELEPHONE                           | +48 22 769 32 26                                                                                                                                                                                                                     |
| EMAIL                                                  | jcw@cnbop.pl                                                                                                         | EMAIL                               | ba@cnbop.pl                                                                                                                                                                                                                          |
| ACCREDITED BY                                          | Polish Centre<br>for Accreditation<br>http://www.pca.gov.pl                                                          | ACCREDITED BY                       | Polish Centre<br>for Accreditation<br>http://www.pca.gov.pl                                                                                                                                                                          |
| AS PER                                                 | EN ISO/IEC 17065<br>Conformity assessment.<br>Requirements for bodies certifying<br>products, processes and services | AS PER                              | EN ISO/IEC 17025<br>General requirements<br>for the competence of testing<br>and calibration laboratories                                                                                                                            |
| VALIDITY                                               | October 3, 2022                                                                                                      | VALIDITY                            | October 11, 2021                                                                                                                                                                                                                     |
| REFERENCE NUMBER                                       | AC 063                                                                                                               | REFERENCE NUMBER                    | AB 207                                                                                                                                                                                                                               |
| CERTIFICATION MARK                                     |                                  |                                     |                                                                                                                                                                                                                                      |
| (ENDORSEMENT) TO BE SIGNED BY MANUFACTURER             |                                                                                                                      |                                     |                                                                                                                                                                                                                                      |
| NAME AND SURNAME<br>OF MANUFACTURERS<br>SIGNATORY      | Ambient-System Sp. z o.o.<br>CEO<br><br>Marcin Starzyński                                                            | SIGNATURE                           | <br>AMBIENT-SYSTEM Sp. z o.o.<br>80-299 Gdańsk, ul. Galaktyczna 37<br>Tel./fax/058/345 51 95; 343 18 77<br>REGON 190061698<br>NIP 584-030-22-20 |
| EMAIL / TELEPHONE                                      | ambient@ambientsystem.pl<br>+48 58 345 51 95                                                                         | FACTORY OFFICIAL SEAL               |                                                                                                                                                                                                                                      |
| NOTES                                                  | I UNDERTAKE THAT ALL DATA AND INFORMATION PROVIDED ARE GENUINE AND ACCURATE.                                         |                                     |                                                                                                                                                                                                                                      |
| (ENDORSEMENT) TO BE CERTIFICATION BODY                 |                                                                                                                      |                                     |                                                                                                                                                                                                                                      |
| NAME AND SURNAME<br>OF CERTIFICATION BODY<br>SIGNATORY | st. bryg. dr inż. Jacek Zboina                                                                                       | SIGNATURE                           | <br>CENTRUM NAUKOWO-BADAWCZE<br>OCHRONY PRZECIWPOŻAROWEJ                                                                                        |
| EMAIL / TELEPHONE                                      | cnbop@cnbop.pl<br>+48 22 769 33 00                                                                                   | CERTIFICATION BODY<br>OFFICIAL SEAL |                                                                                                                                                                                                                                      |
| NOTES                                                  | I UNDERTAKE THAT ALL DATA AND INFORMATION PROVIDED ARE GENUINE AND ACCURATE.                                         |                                     |                                                                                                                                                                                                                                      |

ATTACHEMENT:

COPY OF "CERTIFICATE OF CONSTANCY OF PERFORMANCE" NO. 1438-CPR-0659 ISSUED BY CERTIFICATION BODY