

1X-X3 Compatibility List

Introduction

This document lists the products compatible with your extinguishing and fire alarm control panel.

Compatible products

Table 1: Dx700 series mounting bases and detectors

Model	Description
DB702	Standard mounting base - 100 mm
DB702U	Standard mounting base - 150 mm
DP721I	Optical smoke detector
DP721R	Optical smoke detector with relay
DP721T	Multisensor detector, optical smoke and fixed heat sensors
DP721RT	Multisensor detector with relay, optical smoke and fixed heat sensors
DT713-5	Rate-of-rise heat detector, 57°C, Class A2R
DT713-5R	Rate-of-rise heat detector with relay, 57°C, Class A2R
DT713-7	Rate-of-rise heat detector, 70°C, Class B

Table 2: Manual call points

Model [1]	Description
DM700Bxx-KITR	Blue manual call point, EXTINGUISHING HOLD, push button, with protection cover
DM700KB	Blue manual call point, with key switch
DM702KY	Yellow manual call point, EXTINGUISHING ABORT, with key switch
DMN700B	Blue manual call point
DMN700E100	Red manual call point for outdoor use
DMN700E-IS	Red manual call point, intrinsically safe, for outdoor use
DMN700-EVAC	Red manual call point, EVACUATION
DMN700L	Red manual call point with LED
DMN700LB	Blue manual call point with LED
DMN700R100-KITR	Red manual call point, with resettable element
DMN700Wxx-KITR	White manual call point, EXTINGUISHING ABORT, with protection cover
DMN700Y	Yellow manual call point

Model [1]	Description
DMN700Yxx-KITR	Yellow manual call point, EXTINGUISHING RELEASE, with protection cover
DM860	Red manual call point for fire brigade notification, metal housing
DM860B	Blue manual call point, metal housing
DM865	Red manual call point, metal housing
DM880	Red manual call point, plastic housing
DM880B	Blue manual call point, plastic housing
ZC6-MCP-IS	Red manual call point, intrinsically safe

[1] "xx" represents a language code

Table 3: Sounders and beacons

Model	Description
AS363	Red multitone sounder, shallow base
AS363W	White multitone sounder, shallow base
AS364	Red multitone sounder, deep base
AS364W	White multitone sounder, deep base
AS364WAT	White multitone sounder with anti-tamper design, deep base
AS366	Red multitone sounder and beacon, shallow base
AS366W	White multitone sounder and beacon, shallow base
AS367	Red multitone sounder and beacon, deep base
AS367W	White multitone sounder and beacon, deep base
AS368	Red multitone sounder base
AS368W	White multitone sounder base
AS371	Red sounder and beacon for outdoor use, high output
AS372	Red sounder, intrinsic safe, multitone
AS374	Red horn sounder, hazardous area, multitone
AS376	Red multitone sounder, high output
AS377	Red multitone sounder and beacon, high output
FA340	Xenon beacon, white base, red lens
FA340C	Xenon beacon, white base, clear lens
FA340Y	Xenon beacon, white base, yellow lens
FA350	LED beacon, red shallow base, red lens
FA350WRC	LED beacon, white shallow base, red flash, clear lens

Model	Description
FA350WY	LED beacon, white shallow base, yellow lens
FA350Y	LED beacon, red shallow base, yellow lens
FA355	LED beacon, red deep base, red lens
FA355WRC	LED beacon, white deep base, red flash, clear lens
FA355WY	LED beacon, white deep base, yellow lens
FA360	2J xenon beacon, red shallow base, red lens
FA360B	2J xenon beacon, red shallow base, blue lens
FA360C	2J xenon beacon, red shallow base, clear lens
FA360W	2J xenon beacon, white shallow base, red lens
FA360WB	2J xenon beacon, white shallow base, blue lens
FA360WG	2J xenon beacon, white shallow base, green lens
FA360WY	2J xenon beacon, white shallow base, yellow/amber lens
FA370	LED beacon, intrinsic safe, red lens
FA370C	LED beacon, intrinsic safe, clear lens
FA375	5J xenon beacon, hazardous area, red lens
FA375Y	5J xenon beacon, hazardous area, yellow/amber lens

Table 4: Bells

Model	Description
AB360	6 in. fire bell for indoor use, 24 VDC
AB360-06	6 in. fire bell for indoor use, 24 VDC, Swedish
AB380E	8 in. fire bell for outdoor use, 24 VDC

Table 5: Illuminated signs

Model [1]	Description
GRP25-xx	Illuminated warning sign

[1] "xx" represents a language code

Table 6: Agent release

Model	Description
LPG 24V-11-13W	LPG releasing solenoid (outsourced)

Table 7: Isolation Barriers

Model	Description
GBX370	Galvanic isolator for AS370/FA370 series

Table 8: Door holders and magnets

Model	Description
FE230	Door holder, surface mount, 400 N, with release button
FE235	Door holder, square base, 400 N
FE240	Door holder, flush mount, 400 N
FE245	Door holder, wall mount, 400 N, with release button

Model	Description
FE250	Door holder, floor mounting, 400 N, with release button
FE260-175	Door holder, universal adjustable tube, 400 N, with release button, 175 mm
FE260-325	Door holder, universal adjustable tube, 400 N, with release button, 325 mm
FE260-475	Door holder, universal adjustable tube, 400 N, with release button, 475 mm
FE535	Door holder, steel square base, VdS magnet
FE543	Door holder, reinforced plastic box, VdS magnet
FE550	Door magnet floor mount
FE560	Universal door magnet, adjustable
FE570	Universal door magnet, adjustable
FE581	Door holder, steel square base, IP65, VdS magnet
FE590	Door magnet wall mount, explosion proof

Contact information

For further information on any product listed, contact your local supplier or see www.utcfireandsecurity.com.

Disclaimer

Compatible products may change without notice. Always contact your local supplier to confirm availability and compatibility.

Copyright © 2011 UTC Fire & Security. All rights reserved.