

## Description

5-terminal passive bases are used with 2-wire fire detection and alarm system detectors that do not include additional features, such as remote indicator or alarm relay outputs.

The range of bases provides fire detection and alarm system designers with Standards-compliant, flexible solutions, including models suitable for mounting on solid ceilings with conduit entry points.

## Features

- Secure mounting to all surfaces
- Flexible mounting pitch
- Low profile
- Cable entry points through the rear of the base
- Plated contacts for durable connection to detectors
- Fitted square washer to easy and reliable cable clamping
- Terminals suitable for (0.4 ~ 2.5) mm<sup>2</sup> diameter wiring
- Low maintenance

## Compliance

Bases are approved by conformance assessment agencies as part of the detector compliance (see detector datasheets). The following bases have specific approvals.

	UL
CN3021	✓

## Compatibility Matrix

The following table shows bases and compatible detectors.

Detector \ Base	2-wire Systems	
	CN3021 <sup>a</sup>	CN3023
2-wire non-addressable HNC-310 series, no remote LED, no relay output	O	✓
2-wire non-addressable SNC-300 series, no remote LED, no relay output	O	✓

<sup>a</sup> Required with UL-approved detectors

O — optional

## Ordering Information

Part number	Description	Diameter	Height
CN3021	5-terminal low profile base	102 mm	16 mm
CN3023	5-terminal low profile base	102 mm	16 mm

View the complete range of products at [www.numens.net](http://www.numens.net)



CN3021 / CN3023 low profile 102 mm 5-terminal base